

ELITE SOLDAmaq 30

The band welding machine for the workshop that needs to weld with the "butt welding" system saws of considerable width from 5 to 30 mm (0,19" up to 1,18")



The Elite SOLDAmaq 30 is our bandsaw welding "Push and Go": Just follow the welding parameters we provide you with depending on the thickness and width of the saw, close the saw clamping jaws and push the welding button.

For fast, economical and durable welding of the band saw, ELITE has 4 models of steel band saw welders according to the width we need.

It allows to do both the welding and the annealing of the band saw in one single clamping and without adding any additional material or flux.

The SOLDAmaq EC deburring machine can be used to remove the welding seam.



Can be optionally equipped with
SOLDERAmaq EC deburring machine,
for removal of the weld seam

SPECIFICATIONS

Technical data

Steel bandsaw width	from 5 to 30 mm. (0,2" to 1-1/6")
Bandsaw thickness	from 0,5 to 1 mm. (0,02" to 0,039")
Installed power	4 kW

Available versions

Model	Packing size	Packing weight
SOLDAmaq 30	600 x 800 x 500 mm	52 Kg.

HIGHLIGHTS

- Greater sensitivity in the welding and annealing of thin bands of the stainless steel and bimetal band saw, without additional flux and in a few seconds
- Electronic current control
- Electronic annealing current
- Cutting shear included

We reserve the right to make design changes in the interest of technical progress.
